

P181064

AIR FILTER, PRIMARY FINNED

Why Choose Donaldson Air Filters?

Strong, pliable gasket is compressed against the air cleaner housing to create a tight seal.

- High-efficiency cellulose media performs across a wide range of heavy-duty engine applications.
- Corrosion resistant, coated steel liners support media during operation and help maximize airflow.
- Pleatloc™ feature ensures uniform pleat spacing and prevents media from bunching to promote longer service life.



Attributes

Outer Diameter	7.92 inch (201.1 mm)
Inner Diameter	5.31 inch (134.9 mm)
Length	16 inch (406.4 mm)
Bolt Hole Diameter	0.66 inch (16.76 mm)
Efficiency	99.9
Efficiency Test Std	ISO 5011
Family	FHG
Type	Primary


Style	Finned
Media Type	Cellulose

Packaged Dimensions

Packaged Length	10.7 IN
Packaged Width	10.7 IN
Packaged Height	18.2IN
Packaged Weight	4.38 LB
Packaged Volume	1.2059 FT3

Other Information

Country of Origin	Mexico
NMFC Code	069100-06
HTS Code	8421310000
UPC Code	742330025642

Proposition 65 Notice for California: 
WARNING

This product can expose you to chemicals including Styrene, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.